

MANUFACTURE OF COMPOUND SEMICONDUCTOR DEVICE

Publication number: JP3011634

Publication date: 1991-01-18

Inventor: ONOZUKA ARATA; TANAKA YASUHIRO

Applicant: PETROLEUM ENERGY CENTER FOUND; NIPPON MINING CO

Classification:

- international: **H01L21/314; H01L31/04; H01L21/02; H01L31/04;**
(IPC1-7): H01L21/314; H01L31/04

- european:


Application number: JP19890144069 19890608

Priority number(s): JP19890144069 19890608

[Report a data error here](#)

Abstract of JP3011634

PURPOSE:To form a MIS-type element or the like whose electric characteristic is good and which is stable by a method wherein an oxide film of a III-V compound semiconductor is formed, by using ozone, on the surface of a III-V compound semiconductor which contains In as one constituent element and an insulating film is deposited on it. **CONSTITUTION:**An oxide film of a III-V compound semiconductor is formed, by using ozone, on the surface of a III-V compound semiconductor which contains In as one constituent element; an insulating film is deposited on the oxide film. An ozone oxidation operation is executed while ozone generated by corona discharges 5, 6 flows to the surface of the III-V compound semiconductor. During this process, a temperature of a semiconductor 3 can be selected at about room temperature; it is possible to avoid that the surface of the semiconductor 3 is damaged by heat. Since a dry process is used, a contamination by impurities is not produced. In addition, since the oxidation operation by ozone is caused uniformly and a reaction rate is slow, a dense oxide film is formed. Thereby, it is possible to form a MIS(metal insulator semiconductor) type element or the like whose electric characteristic is good, whose change with the elaps of time is not caused and which is stable.



Data supplied from the **esp@cenet** database - Worldwide